884200

Reviewed on: 04.11.2019 Printing date: 06.12.2019

SECTION 01: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name:

Antique wax (Beeswax solution)

· SDB-group

15470

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation

Surface protection

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Alfred Clouth

Lackfabrik GmbH & Co. KG

Otto-Scheugenpflug-Straße 2

63073 Offenbach/Main

Germany

Tel.: +49 69 - 89 00 7 - 0 / Fax: +49 69 - 89 00 7 - 140

E-Mail: info@clou.de / www.clou.de

· Further information obtainable from:

Laboratory:

Tel.: +49 69 89 00 7 - 104 / Fax: +49 69 89 00 7 - 48104

E-Mail: cosima.sattler@clou.de

• 1.4 Emergency telephone number:

Giftinformationszentrum - Nord

Universitätsklinikum

Bereich Humanmedizin

Robert Koch Str.40

37075 Göttingen

Deutschland

Tel.: + 49 551 / 1 92 40

SECTION 02: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways.

Flam. Liq. 3 - H226 Flammable liquid and vapour.

STOT SE 3 - H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- **Hazard pictograms**







GHS08 GHS02

GHS07

Signal word Danger

· Hazard-determining components of labelling:

(continued on page 2)

884200

Reviewed on: 04.11.2019 Printing date: 06.12.2019

PRODUCT: Antique wax (Beeswax solution)

(continued of page 1)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics / Hydrocarbons, C10-C13, nalkanes, isoalkanes, cyclics, <2% aromatics

Hazard statements

H304 May be fatal if swallowed and enters airways.

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P310 Immediately call a POISON CENTER/doctor.

P370+P378 In case of fire: Use to extinguish: CO2, sand, extinguishing powder.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

- · 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT:

Not applicable.

vPvB:

Not applicable.

SECTION 03: Composition/information on ingredients

🦫 Asp. Tox. 1 - H304

- · 3.2 Mixtures
- Description:

Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS Number % 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, 25-50 cyclics, < 2% aromatics EC number: 919-857-5 Record number 01-2119463258-33 🥸 Asp. Tox. 1 - H304; 🚸 Flam. Liq. 3 - H226: 🕚 STOT SE 3 - H336 64742-48-9 Hydrocarbons, C9-C11, isoalkanes, cyclics, 10-25 <2% aromatics EC number: 920-134-1 Record number 01-2119480153-44 Asp. Tox. 1 - H304; 🚸 Flam. Liq. 3 - H226; 💠 STOT SE 3 - H336; 🧇 Aquatic Chronic 2 - H411 1174522-09-8 Hydrocarbons, C10-C13, n-alkanes, 10-25 isoalkanes, cyclics, <2% aromatics EC number: 918-481-9 Record number 01-2119457273-39

SVHC

(continued on page 3)

884200

Reviewed on: 04.11.2019 Printing date: 06.12.2019

PRODUCT: Antique wax (Beeswax solution)

(continued of page 2)

This product contains no substances in the SVHC list in a concentration > 0,1 %.

Additional information:

For the wording of the listed risk phrases refer to section 16.

SECTION 04: First aid measures

- 4.1 Description of first aid measures
- General information:

Take off or remove contaminated clothing immediately.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Seek medical treatment in case of complaints.

· After skin contact:

Wash thoroughly with soap and water immediately and rinse well.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Do NOT induce vomiting! Keep the patient calm an call a doctor immediately.

· Information for doctor:

Treat symptomatically.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 05: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

• 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- Protective equipment:

Mouth respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Bring if possible, containers from the danger zone. With heating up, printing increase, Berst and danger of explosion.

SECTION 06: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Protection regulations (see point 7 and 8) to consider.

• 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Possible warning the neighbourhood.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(continued on page 4)

884200

Reviewed on: 04.11.2019 Printing date: 06.12.2019

PRODUCT: Antique wax (Beeswax solution)

(continued of page 3)

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 07: Handling and storage

· Handling:

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

Smoking, drinking and eating are not permitted at the working place!

Keep out of the reach of children.

Do not breathe in fumes.

Do not empty into drains.

• Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Vapours are heavier than air.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

The official regulations for the storage of paints and varnishes and Chemicals must be observed.

Information about storage in one common storage facility:

Store away from foodstuffs.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Storage class:

3

7.3 Specific end use(s)

For more information, please refer to the technical data sheet.

SECTION 08: Exposure controls/personal protection

- 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- DNELs

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes,

cyclics, < 2% aromatics

inhalativ, DNEL/DMEL: 900 mg/m3 (Consumer, Long Term Exposure) inhalativ, DNEL/DMEL: 1500 mg/m3 (Worker, Long Term Exposure) Dermal, DNEL/DMEL: 300 mg/kg (Consumer, Long Term Exposure) Dermal, DNEL/DMEL: 300 mg/kg (Worker, Long Term Exposure) Oral, DNEL/DMEL: 300 mg/kg (Consumer, Long Term Exposure)

64742-48-9 Hydrocarbons, C9-C11, isoalkanes, cyclics, <2%

aromatics

inhalativ, DNEL/DMEL: 185 mg/m3 (Consumer, Long Term Exposure) inhalativ, DNEL/DMEL: 871 mg/m3 (Worker, Long Term Exposure) Dermal, DNEL/DMEL: 125 mg/kg (Consumer, Long Term Exposure) Dermal, DNEL/DMEL: 208 mg/kg (Worker, Long Term Exposure) Oral, DNEL/DMEL: 125 mg/kg (Consumer, Long Term Exposure)

(continued on page 5)

884200

Reviewed on: 04.11.2019 Printing date: 06.12.2019

PRODUCT: Antique wax (Beeswax solution)

(continued of page 4)

- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Avoid contact with the eyes and skin.
- Respiratory protection: If the solvent concentration is above WEL limits, a breathing mask approved for this purpose must be worn. Filter A2/P2.
- Protection of hands: The glove material has to be impermeable and resistant to the product the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. Preventive skin protection by use of skin-protecting agents is recommended. Protective gloves made of latex / neoprene. Degradation effect G to E Instalment of permeation E to ND (< 0.9 µg / cm 2 / min). Protective factor index: special subject class 6. Clean skin thoroughly after work and put on skin protecting cream. After use of gloves apply skin-cleaning agents and skin cosmetics.</p>
- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Body protection: Protective work clothing

SECTION 09: Physical and chemical properties

9.1 Information on basic physical and chemical properties

9. I Information on basic physical and che	emicai properties
General Information	
Appearance:	
Form:	Liquid
Colour:	Colourless
Odour:	According to beeswax
Odour threshold:	Not determined.
pH-value:	Not usable on solvent preparations.
Change in condition Phase transfer: fluid	- solid
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	162,0 °C
Flash point (approximately):	48,0 °C DIN 51 755
Flammability (solid, gas):	Not applicable.
Ignition temperature (approximately):	231,00 °C (lowest value of the single components)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0,60 Vol %
Upper:	7,00 Vol %
Oxidising properties	Not determined
Vapour pressure:	Not determined.
Density:	0,7850 g/cm3
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	Organic solvents
water:	Insoluble.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity (according to DIN 53211)	
Dynamic:	Not determined.

(continued on p

884200

Reviewed on: 04.11.2019 Printing date: 06.12.2019

	(continued of page
Kinematic:	< = 20,5 mm2/s (40°C)
Solvent separation test:	< 3 %
Solvent content (approximately):	
Organic solvents (approximately):	86,00 %
VOC (EC)	675,00 g/l
Solids content (approximately):	14,00 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

On storage in containers no traffic laws intolerances are to be expected with the tank shell.

· 10.2 Chemical stability

Stable at room temperature

• Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Forms explosive gases/fumes.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

· 10.4 Conditions to avoid

No further relevant information available.

• 10.5 Incompatible materials:

No further relevant information available.

• 10.6 Hazardous decomposition products:

Flammable gases/vapours

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity
- LD/LC50 values relevant for classification:

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes,

cyclics, < 2% aromatics

Oral, LD50: > 5000 mg/kg (rat) Dermal, LD50: > 5000 mg/kg (Rabbit) Inhalative, LC50/4h: > 5 mg/l (rat)

64742-48-9 Hydrocarbons, C9-C11, isoalkanes, cyclics, <2%

aromatics

Oral, LD50: > 15000 mg/kg (rat)
Dermal, LD50: > 5000 mg/kg (Rabbit)
Inhalative, LC50/4h: > 5000 mg/l (rat)

1174522-09-8 Hydrocarbons, C10-C13, n-alkanes, isoalkanes,

cyclics, <2% aromatics

Oral, LD50: > 5000 mg/kg (rat) Dermal, LD50: > 5000 mg/kg (Rabbit) Inhalative, LC50/4h: > 5 mg/l (rat)

· Primary irritant effect:

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking. Irritant to skin and mucous membranes.

 Serious eye damage/irritation Irritating effect.

 Respiratory or skin sensitisation No sensitising effects known.

Additional toxicological information:

(continued on page 7)

884200

Reviewed on: 04.11.2019 Printing date: 06.12.2019

PRODUCT: Antique wax (Beeswax solution)

(continued of page 6)

The breathing in of solvent proportions above the value of M. W. C.-value can lead to health damages, such as irritating mucous membranes and respiratory organs, kidney and liver damages as well as to the impairment of the central nervous system. Signs and symptoms: Headache, dizziness and tiredness, myasthenia, numbing effect and also unconsciousness in exceptional cases. Longer and repeated skin contact can lead to drying out the skin or to skin irritations, respectively. Solvent splashes can lead to eye irritations and reversible damages. In such cases a physician should be consulted at once.

The product shows the following dangers based on the calculation method of the General EU Classification Guidelines for Substances and Mixtures according to the CLP Regulation in the latest version:

Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways.

STOT SE 3 - H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

· Reproductive toxicity

Based on available data, the classification criteria are not met.

· STOT-single exposure

STOT SE 3 - H336 May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- 12.1 Toxicity
- · Aquatic toxicity:

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes,

cyclics, < 2% aromatics

Dermal, L(E)C50: 2200 mg/l (fish) Dermal, L(E)C50: 2,6 mg/l (daphnie)

64742-48-9 Hydrocarbons, C9-C11, isoalkanes, cyclics, <2%

aromatics

Dermal, L(E)C50: 3,6 mg/l (fish) Dermal, L(E)C50: 22 mg/l (daphnie) Dermal, NOEC: 0,0132 mg/l (fish) Dermal, NOEC: 0,23 mg/l (daphnie)

1174522-09-8 Hydrocarbons, C10-C13, n-alkanes, isoalkanes,

cyclics, <2% aromatics

Dermal, L(E)C50: > 100 mg/l (fish) Dermal, L(E)C50: > 100 mg/l (alga) Dermal, L(E)C50: > 100 mg/l (daphnie) Dermal, NOEC: > 0,1 - 1,0 mg/l (fish) Dermal, NOEC: > 0,1 - 1,0 mg/l (daphnie)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

- Ecotoxical effects:
- Remark:

Harmful to fish

· Additional ecological information:

(continued on page 8)

884200

Reviewed on: 04.11.2019 Printing date: 06.12.2019

PRODUCT: Antique wax (Beeswax solution)

· General notes:

(continued of page 7)

Harmful to aquatic organisms.

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- PBT:

Not applicable.

vPvB:

Not applicable.

· 12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

The mentioned waste code number according to the European waste code catalogue are regarded as a recommendation. A final determining has to be effected in agreement with the regional place of waste disposal as well as the competent authorities.

· Waste disposal key:

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

· European waste catalogue

8 0

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01

wastes from MFSU and removal of paint and varnish

08 01 11

waste paint and varnish containing organic solvents or other hazardous substances $% \left(1\right) =\left(1\right) +\left(1\right) +$

· Uncleaned packaging:

Disposal of uncleaned packagings according to European waste code number 15 01 10.

• Recommendation:

Disposal according to 15 01 04 (metal).

EAK-Nummer 15 01 02 / plastic

Packaging can be reused or recycled after cleaning.

· Recommended cleansing agents:

CLOU Cleaning agent thinner, CLOU Nitro-thinner 790, CLOU DD-29 Thinner

SECTION 14: Transport information

14.1 UN-Number

 ADR
 UN1263

 IMDG
 UN1263

 IATA
 UN1263

ADR 1263 PAINT (HYDROCARBONS, C9-C11, N-ALKANES,

ISOALKANES, CYCLICS, < 2% AROMATICS)

IMDG PAINT IATA PAINT

· 14.3 Transport hazard class(es)

ADR

Class 3 (F1) Flammable liquids.

(continued on page 9)

GB

884200

Reviewed on: 04.11.2019 Printing date: 06.12.2019

PRODUCT: Antique wax (Beeswax solution)

Label

(continued of page 8)

IMDG

Class 3 Flammable liquids.

Label

Label



3 Flammable liquids.

IATA Class

3

· 14.4 Packing group

ADR III
IMDG III
IATA III

• 14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user

Warning: Flammable liquids.

Danger code (Kemler): 30

EMS Number: F-E,S-E

- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
- Transport/Additional information:

Not applicable.

 Excepted quantities (EQ):
 E1

 Limited quantities (LQ)
 5L

 Transport category
 3

 Tunnel restriction code
 D/E

 IMDG

Limited quantities (LQ) 5L Excepted quantities (EQ) E1

• UN "Model Regulation":

UN 1263 PAINT (HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS), 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to EU guidelines:

(continued on page 10)

884200

Reviewed on: 04.11.2019 Printing date: 06.12.2019

PRODUCT: Antique wax (Beeswax solution)

(continued of page 9)

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

• REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3, 40

· National regulations:

· Information about limitation of use:

Pregnant and breastfeeding women and young persons.

· 15.2 Chemical safety assessment:

For this product no appraisal of substance safety was carried out. Information from exposure scenarios of the following substances were integrated into section 1-16:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

The compliance with the application conditions and measures for risk minimisation contained in this material safety data sheet ensures the conformity with the existing exposure scenarios.

Storage class:

3

SECTION 16: Other information

Other information:

· Reasons for changes

Under point 3 a substance has been removed.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing MSDS:

Laboratory / Department of Material Safety Data Sheets:

Phone: +49 69 89 00 7 - 104 / Fax: +49 69 89 00 7 - 48104/

E-Mail: cosima.sattler@clou.de

Information:

The information given in this safety data sheet is based on the present level of knowledge, but does not represent an assurance of product characteristics.

The user is responsible for observing all necessary legal regulations.

For further information on the handling and application of the product(s), please refer to our label and the technical instructions leaflet or contact our Customer Service Department on Tel.: +49 69 / 89 00 7 -124, -107 or -227.

According to § 14 GefStoffV the employer must provide instruction to the employees affected on the basis of the operating instructions every year. The content and time of the instruction is to be recorded in writing and confirmed by signatures from those receiving instruction.

Please observe work safety measures in items 8 and 15.

Use only for intended purposes. Keep out of the reach of children.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

(continued on page 11)

Page: 11 / 11

Safety data sheet as per 1907/2006/EC, Article 31

884200

Reviewed on: 04.11.2019 Printing date: 06.12.2019

PRODUCT: Antique wax (Beeswax solution)

(continued of page 10)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.