



TECHNICAL DATA SHEET

rev. 00 2006/07/05

**CARVER SEAL (sealant)**

code 3090

**TECHNICAL DATA** (based on room temperature of +23°C and 65% of relative air humidity)

Appearance	coloured paste
Application temperature	from 5°C to 45°C
Open time	30 min.
Drying time (5 mm depth)	4 - 5 h.
Overcoating after	24 h.
Sanding after	24 h.
Foot traffic after	24 h.
Packaging	300 cc cartridge

**DESCRIPTION**

Acrylic sealant, designed for filling fissures and cracks in wooden floors; suitable for joints between floor and baseboard, gaps in front of the doorsteps, etc..

The product is plastoelastic, VOC-free and odourless. Can be sanded and overcoated with floor finishes.

CARVER SEAL is available in the following colours: oak, doussié, teak (suitable also for light iroko and cabreuva), ipé (suitable also for dark iroko).

**SURFACE PREPARATION**

The surfaces to be treated should be clean and dry.

**DIRECTIONS**

Cut the tip of the threaded end, then screw on the nozzle. Apply the sealant by means of a cartridge gun and smooth it with an even spatula. Not to stain the edges, it is recommended to protect them with masking tape, that should be removed immediately after application.

**NOTICE**

- Fresh sealant residues are easily eliminated with Carver NET PARQUET stain-remover, whereas once hardened, the product can be removed only mechanically.
- During hardening, work area must be ventilated.
- Fresh product may cause irritation to skin. In case of contact, wash the interested area with soap and water.

**Dispose of excess product and empty containers properly.**

**If the original unopened container is stored in a cool and dry place, the product will keep for at least 24 months.**

*The information contained in this technical data sheet is to the best of our knowledge and experience. Since the conditions of use are beyond our control, no warranty is given or implied.*